

Dynaric Stainless Steel Machines

Fulfilling Packaging and
Strapping Requirements
in Harsh Environments
such as the **Poultry,**
Meat, Seafood, and
Agricultural Industries



Dynaric, Inc.



®

5740 Bayside Road, Virginia Beach, VA 23455

Phone: (800) 526-0827 Fax: (757) 363-8016

E-mail: gd@dynaric.com

Web address: www.dynaric.com

Dynaric Stainless Steel Machines

- Anti-jam feature eliminates strap jams in unit*
- Internal dispenser (except for the ST1SS); minimizes required floor space, keeps strap dry
- Available in 220 volts, 3-phase with optional 110 volt, single phase or 460 volt, 3-phase
- An electronic control pad allows the operator to easily adjust timer functions, heater temperature setting and seal time*
- Digital display reflects the unit's operational status, including an error read-out for easy troubleshooting*
- Easy strap feeding and adjustable external tension control and heat seal allows operators to strap packages in easy, efficient manner
- Easily adjustable table height for a variety of conveyor configurations
- Energy saving feature; motor automatically shuts down when machine is not in use
- Mobile; casters allow for the machine to be easily moved throughout your facility
- Available for use with 3/8" or 1/2" strapping

* Not available on DF-207S Side Seal, Semi-Automatic Model

SPECIFICATIONS	DF207S	DF11S	DF11SA	DF11SC	DF11SCA	DF117S	DF117SA	ST1SS
Arch Size: Standard	N/A	27.6"Wx15.75"H	27.6"Wx15.75"H	27.6"Wx15.75"H	27.6"Wx15.75"H	27.6"Wx23.6"H	27.6"Wx15.7"H	23.6"Wx19.6"H
	Other arch sizes available and will be quoted upon request							
Width	39.4"	25.6"	25.6"	25.6"	25.6"	25.6"	46.65"	23.9"
Length	23.6"	44.7"*	44.7"*	44.7"*	44.7"*	65.8"*	63.4"	59.5"
Height	32.6"	53.0"*	53.0"*	53.0"*	53.0"*	52.6"*	49.5"	63.6"
Table Height	32.8" - 34.0"	31.3"	31.3"	31.3"	31.3"	26.3" - 28.7"	25.2" - 26.0"	52.8"
Weight	209 lbs.	407 lbs.*	440 lbs.*	407 lbs.*	440 lbs.*	506 lbs.*	771 lbs.*	825 lbs.
Cycle Time	2.0 sec.	1.6 sec. *	1.6 sec. *	1.6 sec. *	1.6 sec. *	1.6 sec. *	1.6 sec. *	1.6 sec. *
Tension	7 to 120 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	0 to 73 lbs.
Maximum Pkg. Size	Depending on Arch Size							
Minimum Pkg. Size	3.9"H x 2.4"W	1.8"H x 3.1"W	1.8" H x 8.5" W	1.8" H x 3.1" W	1.8" H x 8.5" W	2.8" H x 5.9" W	1.2" H x 1.6" W	.39" H x 3.9" W
Seal Head Location	Side	Bottom	Bottom	Bottom	Bottom	Side	Side	Bottom
Cycle Start								
Foot Switch		●		●		●		
Push Button		●	●	●	●	●	●	●
Photocell			●		●		●	●
Strap Insert	●							
Table Conveyor								
Gravity Rolls	●	●		●		●		
Power Belts			●		●		●	●
Corrosion Resistance								
Cabinet	●	●	●	●	●	●	●	●
Internal	●	●	●			●	●	●
Arch	●	●	●	●	●	●	●	●

*Dependent upon arch size



5740 Bayside Road, Virginia Beach, VA 23455

Phone: (800) 526-0827 Fax: (757) 363-8016

E-mail: gd@dynaric.com

Web address: www.dynaric.com